

S606B/S606c 導熱膏 Thermal Grease



產品特性 Features

Good thermal conductivity 良好的導熱性
Easy to assemble 容易施工
High stability 高穩定性
Would not harden 不乾硬化

產品應用端 Applications

Electronic components: IC, CPU, MOS
LED, M/B, P/S, Heat Sink, LCD-TV
Notebook, PC, Telecom Device, Wireless Hub.....etc.
DDR II Module, DVD Applications, Hand-set Applications.....etc.


保存方式 Storage

S606 has a shelf-life of eighteen (18) months from the date of manufacture, as indicated by the lot number, when stored in the original, unopened contained at, or below 25°C.

S606 系列在其未開封之狀態 · 於室溫25°C以下可保存18個月 ·

產品物性 Properties

● REACH Compliant 符合REACH規範 ● RoHS Compliant 符合RoHS規範



S606B Thermal Conductivity 導熱係數: 1.8 W/m.K
S606c Thermal Conductivity 導熱係數: 5.0 W/m.K

Properties	S606B	S606c	Unit	Tolerance	Test Method
Thermal Conductivity 導熱係數	1.8	5	W / mK	±10	ASTM D5470
Color 顏色	White白	Gray灰	-	-	Visual目視
Oil Dispersible油分離度	<0.2	<0.05	%	-	24hrs at 150°C
Weight Loss重量損失	<0.5	<0.5	%	-	ASTM E595
Specific Gravity比重	2.3	2.3	g / cm3	±10%	ASTM D792
Working Temperature工作溫度	-40~+180	-40~+180	°C	-	-
Viscosity黏度	30	125	Pas	-	ASTM D2196
Standard package標準包裝	1KG	1KG	Pot	-	-
Volume Resistance體積阻抗	>10 ¹²	>10 ¹²	Ohm-cm	-	ASTM D257
Thermal Resistance熱阻值	0.06	0.02	°C - in / W	-	ASTM D5470

Need samples? 樣品需求?

S6060c - 30 gram

1	2
---	---

1. Choose the P/N
2. Fill the quantity you need